

PRODUCT DATA SHEET BRIGHTER ATOM WC

A very powerful and effective LED strobe with popular and valued characteristics, in the Colour version, equipped with 648 LEDs with a power of 0.6 W RGB. The main advantage of the device is the independent control of 6 LED sections, which significantly extends the effects possibilities. It has a high-class dimmer that allows you to control the brightness according to 6 curves. The Atom Strobe series strobe with IP65 waterproof class can work safely in all conditions. The device is equipped with Powercon, XLR IP65 sockets. Comes with a stand and barndoors.

Electrical Parameters:

Maximum Power Consumption: 450W

Light Source: 648x 0,6W RGB 3-in-1 LED

Estimated Light Source Lifespan: 50 000h

Power Supply Voltage: 100-240V, 50/60Hz

Features and Functions:

Beam Angle: 120°

Operating Modes: DMX512, Auto, Master/Slave

Dimmer: electronic 0-100%

6 different brightness control curves

Movement Range: 170° tilt

DMX Channels: 3/9/24

Physical Parameters:

Protection Level: IP65

Dimensions: 497x316x170mm

Weight: 11 kg

Power Supply Sockets Standard: PowerCon (IN/OUT)

DMX Sockets: 3-pin

The above-mentioned device, which is the subject of this product specification, complies with the relevant requirements of Union harmonization legislation.

EN 55015:2013

EN 61547:2009

EN 61000-3-2:2006+A1:2009+A2:2009

EN 61000-3-3:2013