

PRODUCT DATA SHEET

BRIGHTER QUADRO BLIND

A modern device replacing classic blinders, based on four COB LEDs, 100W each. Thanks to the LED technology used, the device has a very long service life, which can be a big problem in the case of classic incandescent blinders. Quadro Blind allows linear adjustment of the virtual inertia of the dimmers as desired, and the ability to control each LED independently. The device is produced in three variants of colour temperature: 2500K, 3200K and 5600K.

Electrical Parameters:

Maximum Power Consumption: 400W

Light Source: 4x 100W COB LED

Estimated Light Source Lifespan: 50 000h

Power Supply Voltage: 100-240V, 50/60Hz

Physical Parameters:

Protection Level: IP20

Power Supply Sockets Standard: PowerCon (IN/OUT)

DMX Sockets: 3-pin and 5-pin

Features and Functions:

Beam Angle: 60°

Operating Modes: DMX512, Master/Slave, Sound Active

Dimmer: electronic 0-100%

Colour temperature: 2500K/3200K/6500K

DMX Channels: 2/8 and 3/9

The above-mentioned device, which is the subject of this product specification, complies with the relevant requirements of Union harmonization legislation.

EN 55015:2013

EN 61547:2009

EN 61000-3-2:2006+A1:2009+A2:2009

EN 61000-3-3:2013