

## PRODUCT DATA SHEET BRIGHTER LUMO IP

A modern replacement for the classic blinder, based on the COB 540W LED. Thanks to the LED technology used, this fixture has a very long service life, which can be a big problem in the case of classic incandescent blinders. Lumo IP also has an LED ring that can be used to create an eye-candy effect. All the features listed above closed in light IP65 housing

### Electrical Parameters:

**Maximum Power Consumption:** 350W

**Light Source:** 6x90W COB LED RGBLAC +32x0,2W LED RGB

**Estimated Light Source Lifespan:** 50 000h

**Power Supply Voltage:** 100-240V, 50/60Hz

### Features and Functions:

**Beam Angle:** 55°

**Operating Modes:** DMX512, RDM, Master/Slave, Sound Active

**Dimmer:** electronic 0-100%

**Colour temperature:** 1800K-8500K

**DMX Channels:** 1/2/3/6/9/13/17/19/23

**Possibility to connect devices to each other**

### Physical Parameters:

**Protection Level:** IP65

**Dimensions:** 235x249x193mm

**Weight:** 3,4kg

**Power Supply Sockets Standard:** PowerCon TRUE1 (IN/OUT)

**DMX Sockets:** 3-pin

The above-mentioned device, which is the subject of this product specification, complies with the relevant requirements of Union harmonization legislation.

EN 55015:2013

EN 61547:2009

EN 61000-3-2:2006+A1:2009+A2:2009

EN 61000-3-3:2013