

PRODUCT DATA SHEET

BRIGHTER LUMO IP

A modern replacement for the classic blinder, based on the COB 540W LED. Thanks to the LED technology used, this fixture has a very long service life, which can be a big problem in the case of classic incandescent blinders. Lumo IP also has an LED ring that can be used to create an eye-candy effect. All the features listed above closed in light IP65 housing

Electrical Parameters:

Maximum Power Consumption: 350W

Light Source: 6x90W COB LED RGBLAC +60x0,2W LED RGB

Estimated Light Source Lifespan: 50 000h

Power Supply Voltage: 100-240V, 50/60Hz

Features and Functions:

Beam Angle: 55°

Operating Modes: DMX512, RDM, Master/Slave, Sound Active

Dimmer: electronic 0-100%

Colour temperature: 1800K-8500K

DMX Channels: 1/2/3/6/9/13/19/19/25

Possibility to connect devices to each other

Physical Parameters:

Protection Level: IP65

Dimensions: 235x249x193mm

Weight: 3,4kg

Power Supply Sockets Standard: PowerCon TRUE1 (IN/OUT)

DMX Sockets: 3-pin

The above-mentioned device, which is the subject of this product specification, complies with the relevant requirements of Union harmonization legislation.

EN 55015:2013

EN 61547:2009

EN 61000-3-2:2006+A1:2009+A2:2009

EN 61000-3-3:2013