

## PRODUCT DATA SHEET

# BRIGHTER X-BAR

Powerful LED Bar with innovative RGBL colour mixing, Full pixel control and IP65 waterproof body. Equipped with beam optics it will throw the light at a very long range. Beam angle can be adjusted by variety of different frostfilters. Silent cooling system will keep the device in safe conditions, without annoying anyone on the stage. Up to 500W of light for your show.

### Electrical Parameters:

**Maxium Power Consumption:** 500W

**Light Source:** 18x25W RGBL LED

**Estimated Light Source Lifespan:** 50 000h

**Powern Supply Voltage:** 100-240V, 50/60Hz

### Features and Functions:

**Total lumen output:** 7200Lm

**Lux:** 30500 lux @3m (6°, RGBL),

**Beam angle:** 6°/10°/20° +Frost Filter

**Operating modes:** DMX512/ArtNet/sACN/RDM/Manual

**Dimmer:** eletronic 0-100%

**Ability to independently control each diode**

**DMX Channels:** 4/10/20/33/37/77

### Physicial Parameters:

**Protection Level:** IP65

**Dimensions:** 1000x210x85mm

**Weight:** 10,5 kg

**Power Sockets:** PowerCon TRUE1 (IN/OUT)

**DMX Sockets:** 3-pin

**Art-Net Sockets:** RJ45

The above-mentioned device, which is the subject of this product specification, complies with the relevant requirements of Union harmonization legislation.

EN 55015:2013

EN 61547:2009

EN 61000-3-2:2006+A1:2009+A2:2009

EN 61000-3-3:2013