

## PRODUCT DATA SHEET BRIGHTER X-BAR IP

Powerful LED Bar with innovative RGBL colour mixing, Full pixel control and IP65 waterproof body. Equipped with beam optics it will throw the light at a very long range. Beam angle can be adjusted by variety of different frostfilters. Silent cooling system will keep the device in safe conditions, without annoying anyone on the stage. Up to 500W of light for your show.

### Electrical Parameters:

**Maximum Power Consumption:** 500W

**Light Source:** 18x25W RGBL LED

**Estimated Light Source Lifespan:** 50 000h

**Power Supply Voltage:** 100-240V, 50/60Hz

### Features and Functions:

**Total lumen output:** 7200lm

**LUX:** 30500@3m (6° RGBL)

**CRI:** >80Ra (2000K-8000K)

**TLCI:** 82@3200K, 86@5600K

**TM-30 Rf:** 87@3200K, 85@5600K

**TM-30 Rg:** 109@3200K, 109@5600K

**Beam Angle:** 6° + Frost Filters 10x60°/20°/45°

**Operating Modes:** DMX512/Art-Net/sACN/RDM/Manual

**Ability to independently control each diode**

**DMX Channels:** 4/10/20/33/37/77

### Physical Parameters:

**Protection Level:** IP65

**Dimensions:** 1000x210x85mm

**Weight:** 10,5 kg

**Power Supply Sockets Standard:** PowerCon TRUE1 (IN/OUT)

**DMX Sockets:** 5-pin

**Art-Net Sockets:** RJ45

The above-mentioned device, which is the subject of this product specification, complies with the relevant requirements of Union harmonization legislation.

EN 55015:2013

EN 61547:2009

EN 61000-3-2:2006+A1:2009+A2:2009

EN 61000-3-3:2013