

PRODUCT DATA SHEET

BRIGHTER X-STROBE IP

The Brighter X-Strobe IP is the perfect solution, combining a powerful strobe with an effective pixel-mapping light. The X-Strobe IP also features movement with a 180° tilt range, allowing you to create amazing lighting effects. The user has access to 120 independently controlled sections (24xRGBWW and 96xCW), and the built-in Art-Net/sACN. In order to adapt the device to harsh working conditions, it has been designed to maintain the protection rating at IP65.

Electrical Parameters:

Maximum Power Consumption: 1900 W

Light Source: 864x1,6W RGBWW LED + 576x1W CW LED

Estimated Light Source Lifespan: 30 000h

Power Supply Voltage: 100-240V, 50/60Hz

Features and Functions:

Lux: 3420@3m (RGBWW+CW)

Beam Angle: 140°

Operating Modes: DMX512, Art-Net, sACN, RDM, Manual

Dimmer: electronic 0-100%

Movement Range: 180° tilt

Ability to independently control 120 sections (24xRGBWW+96xCW)

DMX Channels: 3/4/15/21/27/105/108/198

Physical Parameters:

Protection Level: IP65

Dimensions: 493x175x200mm

Weight: 14 kg

Power Supply Sockets Standard: PowerCon TRUE1 (IN/OUT)

DMX Sockets: 3-pin

Art-Net Sockets: RJ45

The above-mentioned device, which is the subject of this product specification, complies with the relevant requirements of Union harmonization legislation.

EN 55015:2013

EN 61547:2009

EN 61000-3-2:2006+A1:2009+A2:2009

EN 61000-3-3:2013