brighter

PRODUCT DATA SHEET BRIGHTER X-PROFILE IP

Brighter X-Profile IP is an extremaly bright, professional, profile movig head. Based on 800W LED egnine, could be used as beam, spot, wash and profile. 2 gobo wheels, prism, animation disk, frost filter, linear CTO filter, HI-CRIi filter, 4 electronic framing blades, silent operation mode and CMY colour mixing provides everything you need wherever you need it. All the features listed above, closed in the slim, elegant IP65 housing.

Electrical Parameters:	Prism: 3-facet circular
Maximum Power Consumption: 850W	Frost Filter: yes
Light Source: 800W LED	Strobe: 1-25 Hz
Estimated Light Source Lifespan: 50 000h	Operating Modes: DMX512/ArtNet/sACN/RDM/Manual
Power Supply Voltage: 100-240V, 50/60Hz	Physical Parameters:
Features and Functions:	Protection Level: IP65
Colour mixing: CMY	Dimensions: 405x310x760mm
Colour wheel: 5 colors + white	Weight: 37 kg
HI-CRI filter	Power Supply Sockets Standard: PowerCon TRUE1 (IN/OUT)
CRI: >70Ra(>90Ra with HI-CRI filter)	DMX Sockets: 3-pin Art-Net Sockets: RJ45
CTO: 3000K-8000K	
Zoom: 6°-50°	
Dimmer: electronic 0-100%	
Movement Range: 540°/270° pan/tilt	
4- blade framing system	
Gobo wheels: 7 rotating and 11 static effects	
Animation Disk: yes	
Iris: mechanical	

The above-mentioned device, which is the subject of this product specification, complies with the relevant requirements of Union harmonization legislation.

EN 55015:2013 EN 61547:2009 EN 61000-3-2:2006+A1:2009+A2:2009 EN 61000-3-3:2013