brighter

product data sheet BRIGHTER EYE 1500 PRO

Brighter EYE 1500 PRO is a powerful Wash. Thanks to the independent control of the LED rings and the motorized zoom mechanism makes it a versatile and universal device. In combination with powerful, 25W RGBW LED chips, the device becomes a very interesting proposition for large concert and theatre stages.

Electrical Parameters:

Maximum Power Consumption: 850W Light Source: 37x 25W 4-in-1 RGBW LED Estimated Light Source Lifespan: 50 000h Power Supply Voltage: 100-240V, 50/60Hz

Physical Parameters:

Protection Level:: IP20

Dimensions: 400x200x465mm

Weight: 17 kg

Power Supply Sockets Standard: PowerCon TRUE1 (IN/OUT)

DMX Sockets 3-pin and 5-pin

Features and Functions:

Total lumen output: 13940m

Lux: 41500@3m(RGBW, Zoom Narrow) 3800@3m(RGBW, Zoom Wide)

Movement Range: 540°/270° pan/tilt

Zoom: 10°-60°

Operating Modes: DMX512, Sound Active, Master/Slave

Dimmer: electronic 0-100%

DMX Channels: 19/36

The above-mentioned device, which is the subject of this product specification, complies with the relevant requirements of Union harmonization legislation.

EN 55015:2013 EN 61547:2009 EN 61000-3-2:2006+A1:2009+A2:2009 EN 61000-3-3:2013