

PRODUCT DATA SHEET

BRIGHTER PROFILE 300 ZOOM+

Brighter LED PROFILE 300+ ZOOM is a high-class profile illuminator equipped with a 400W LED multicolor light source in COB technology, available in two variants of the lighting angle adjustment range: 15°-28° and 20°-45°. It achieves high light intensity parameters and superior color mixing. The LED PROFILE series is characterized by an advanced cooling system that allows for silent operation. The illuminator is made of durable and solid metal alloys, thanks to which it will work in difficult conditions for many years. The design of the device allows the replacement of optics without disassembling the part containing the light source.

Electrical Parameters:

Maximum Power Consumption: 350W

Light Source: 400W RGBALC COB LED

Estimated Light Source Lifespan: 50 000h

Power Supply Voltage: 100-240V, 50/60Hz

Physical Parameters:

Protection Level: IP20

Dimensions: 790x315x320mm

Weight: 9,2 kg

Power Supply Sockets Standard: PowerCon (IN/OUT)

DMX Sockets: 3-pin and 5-pin

Features and Functions:

Beam angle: 15°-28° / 20°-45°

Dimmer: Electronic 0-100%

Operating Modes: DMX512, Manual

DMX Channels: 6/10

Wymienione powyżej urządzenie będące przedmiotem niniejszej specyfikacji produktu, jest zgodne z odnośnymi wymaganiami unijnego prawodawstwa harmonizacyjnego.

EN 55015:2013

EN 61547:2009

EN 61000-3-2:2006+A1:2009+A2:2009

EN 61000-3-3:2013